## FLOS




## Bellhop Bollard H 850 mm Dimmable 1-10V White

Bollard version of the Bellhop Outdoor Collection for diffuse light. Made of extruded and die-cast aluminium or stainless steel, Bellhop is available in two heights for the bollard model and with different lumens and luminaire outputs as to comply with any outdoor setting and lighting scenario need. 220-240V power supply included. Ready for installation on solid surface.

Each luminaire is equipped with 200 mm cable for connection inside the luminaire...





Luminous flux luminaire 551 lm

Mountings	Ground
Lamp category	LED
Power (W)	8
Colour temperature	2700K
CRI	80
Lumen	551 lm
Voltage (V)	230
Environment	Outdoor
LED type	Power LED
Aiming	Fixed
Light Distribution	Symmetric
Beam Angle	85
Transformer Availability	Included
Transformer Mounting	Integrated
Transformer Type	Electronic dimmable
	1-10V
Emergency	Without
Insulation Class	I
Lamp Holder	LED
Dimmable	Yes
Colors	F003B21B001 - White
Certificates	
Note	During the installation and

## FLOS

## 058 Ø55 Ø125

the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating. Damages on the coating exposed to outdoor conditions or water, could cause corrosion. Chemical substances affect the anticorrosion covering protection. For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges These effects are frequently caused by: • over voltage coming from the mains' network where fixture is connected. • electrostatic discharge (ESD) coming from the environment. The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.