FLOS




Belvedere Clove 2 Dimmable 1-10V Black

Family of outdoor products consisting of luminaires with a pole of two different heights and suitable for floor installations (ground or buried) and with integrated power supply box.


220-240V power supply included. Ready for installation on solid surface. Box for ground installation to be ordered separately. Included 2 way terminal block 4 poles IP68 H2O Stop.

Version 110V upon request.





Luminous flux luminaire 657 lm



Mountings Lamp category Power Colour temperature CRI Lumen Voltage (V) Environment	Ground LED 8.4 3000K 80 657 lm 230 Outdoor
LED type Aiming Light Distribution Beam Angle	Power LED Fixed Symmetric 100
Transformer Availability Transformer Mounting Transformer Type Emergency Insulation Class Lamp Holder	Included Integrated Electronic dimmable 1-10V Without II I FD
Dimmable	Yes
Colors	F001B31B030 - Black
Certificates	CEDV
Note	We recommend using a connection system with a degree of protection

FLOS


greater than or equal to the degree of protection of the luminaire. During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating. Damages on the coating exposed to outdoor conditions or water, could cause corrosion. Chemical substances affect the anticorrosion covering protection. For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges These effects are frequently caused by: • over voltage coming from the mains' network where fixture is connected. • electrostatic discharge (ESD) coming from the environment. The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.



Belvedere Clove 2 Dimmable 1-10V Black



Box for ground installation F001Z020000



S.P.D. (SURGE PROTECTION DEVICE) F990E00A000