




## Superarchimoon outdoor Panama

Floor lamp for outdoor use providing direct and dif-fused light. External diffuser obtained from braided colored PVC tubes, internal frame in polyester-painted aluminum tubular. Internal diffuser in injection-molded opal polycarbonate.


The structural parts of the luminaire (base support, diffusers support, arms, brackets, levers and tie rods) have been treated with a chemical conversion for enhanced weather resistance. The body is painted in grey....





Beam Angle DIR: 78°		
h(m)	E( <b>İ</b> ×)	D(m)
1	118	1.63
2	30	3.26
3	13	4.89
4	7	6.53
5	5	8 1 6

Luminous flux luminaire 4350 lm



Mountings	Floor
Voltage (V)	230
Environment	Outdoor
Aiming	Adjustable
Light Distribution	Symmetric
Beam Angle	78
Emergency	Without
Insulation Class	II
Lamp Holder	E27
Colors	🚇 F6367022 - Panama
Certificates	
Note	Light source not included. HSGS E27: 1x250W or 1 LED: 21W - 2450 lm - 3000K We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.



## Superarchimoon outdoor Panama



LED 21W E27 2450lm 3000K DIMMER RF26998