



## Superarchimoon outdoor Green wall

Floor lamp for outdoor use providing direct and dif-fused light. External diffuser obtained from braided colored PVC tubes, internal frame in polyester-painted aluminum tubular. Internal diffuser in injection-molded opal polycarbonate.

The structural parts of the luminaire (base support, diffusers support, arms, brackets, levers and tie rods) have been treated with a chemical conversion for enhanced weather resistance. The body is painted in grey....




<b>Mountings</b>	Floor
<b>Voltage (V)</b>	230
<b>Environment</b>	Outdoor

<b>Aiming</b>	Adjustable
<b>Light Distribution</b>	Symmetric
<b>Beam Angle</b>	74

<b>Emergency</b>	Without
<b>Insulation Class</b>	II
<b>Lamp Holder</b>	E27


**Colors** F6367041 - Green Wall



Beam Angle DIR: 74°

h(m)	E(lx)	D(m)
1	88	1.50
2	22	3.01
3	10	4.51
4	6	6.02
5	4	7.52

Luminous flux luminaire  
4350 lm



## Certificates



## Note

Light source not included.  
HSGS E27: 1x250W or 1  
LED: 21W - 2450 lm -  
3000K We recommend  
using a connection system  
with a degree of  
protection greater than or  
equal to the degree of  
protection of the  
luminaire.

## Superarchimoon outdoor Green wall



---

LED 21W E27 2450lm 3000K  
DIMMER  
RF26998