



## Belvedere Spot Pick Non Dimmable Grey

Family of adjustable outdoor LED lighting luminaires (double rotation, vertical and horizontal axle) suitable for floor installations (ground or buried) and with integrated power supply box.

220-240V power supply included. Included 2 way terminal block 4 poles IP68 H2O Stop.

24V Dimmable version available on request.

Version 110V upon request.



90°			7	90°
H		X	Z	$\rightarrow$
60° ×	///	$\forall$	$\langle \rangle$	60°.
K/	$\not\vdash$	4	eg	>
$\bigvee$	/	-+		$\setminus$
30°	6064	1 cd	1	30°

Luminous flux luminaire 425 lm

Bea	10°	
h(m)	) E(Ix)	D(m)
1	6064	0.17
2	1516	0.34
3	674	0.51
4	379	0.68
5	243	0.84

**Mountings** Ground spike

Lamp categoryLEDPower6Voltage (V)230EnvironmentOutdoor

LED typePower LEDAimingAdjustableLight DistributionSymmetric

Beam Angle 10

Transformer Availability
Transformer Mounting
Transformer Type
Emergency
Insulation Class
Lamp Holder
Dimmable
Included
Not dimmable
Integrated
Not dimmable
Leb
No

**Colors** F001F21A006 - Grey

Note

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire. During

the installation and the





maintenance of the fixtures it is important to be careful and avoid damages on the paint coating. Damages on the coating exposed to outdoor conditions or water, could cause corrosion. Chemical substances affect the anticorrosion covering protection. For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges These effects are frequently caused by: • over voltage coming from the mains' network where fixture is connected. • electrostatic discharge (ESD) coming from the environment. The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.



## Belvedere Spot Pick Non Dimmable Grey









Spot visor F001Z010000 Spot visor with honeycomb F001Z030000

Spot visor with flood lens F001Z040000

S.P.D. (SURGE PROTECTION DEVICE) F990E00A000