



Belvedere Spot Pick Non Dimmable Deep Brown

Family of adjustable outdoor LED lighting luminaires (double rotation, vertical and horizontal axle) suitable for floor installations (ground or buried) and with integrated power supply box.

220-240V power supply included. Included 2 way terminal block 4 poles IP68 H2O Stop.

24V Dimmable version available on request.

Version 110V upon request.



90°				
60°				
KX4IIIXX				
30° $\sqrt{3225}$ cd $\sqrt{30^{\circ}}$				
Luminaua flux luminaira				

Luminous flux luminaire 380 lm

Beam Angle:		17°
h(m)	E(lx)	D(m)
1	3225	0.29
2	806	0.59
3	358	0.88
4	202	1.18
Е	120	1 17

h(m)	E(lx)	D(m)
1	3225	0.29
2	806	0.59
3	358	0.88
4	202	1.18
5	129	1.47

Ground spike Mountings

Lamp category LED **Power** 6 230 Voltage (V) **Environment** Outdoor

Power LED LED type **Aiming** Adjustable **Light Distribution** Symmetric

Beam Angle 17

Transformer Availability Included **Transformer Mounting** Integrated Not dimmable **Transformer Type** Without **Emergency** Ш **Insulation Class** Lamp Holder **LED** Dimmable No

Colors F001F22A018 - Deep Brown

Certificates

Note



We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire. During the installation and the



maintenance of the fixtures it is important to be careful and avoid damages on the paint coating. Damages on the coating exposed to outdoor conditions or water, could cause corrosion. Chemical substances affect the anticorrosion covering protection. For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges These effects are frequently caused by: • over voltage coming from the mains' network where fixture is connected. • electrostatic discharge (ESD) coming from the environment. The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.



Belvedere Spot Pick Non Dimmable Deep Brown









Spot visor F001Z010000 Spot visor with honeycomb F001Z030000

Spot visor with flood lens F001Z040000

S.P.D. (SURGE PROTECTION DEVICE) F990E00A000