## FLOS




## Belvedere Spot Pick Non Dimmable White

Family of adjustable outdoor LED lighting luminaires (double rotation, vertical and horizontal axle) suitable for floor installations (ground or buried) and with integrated power supply box.

220-240V power supply included. Included 2 way terminal block 4 poles IP68 H2O Stop.

24V Dimmable version available on request. Version 110V upon request.





Beam Angle:		28°
h(m)	E(I×)	D(m)
1	1192	0.50
2	298	1.01
3	132	1.51
4	74	2.01
5	48	2.51

Luminous flux luminaire 351 lm



Mountings	Ground spike
Lamp category	LED
Power	6
Voltage (V)	230
Environment	Outdoor
LED type	Power LED
Aiming	Adjustable
Light Distribution	Symmetric
Beam Angle	28
Transformer Availability	Included
Transformer Mounting	Integrated
Transformer Type	Not dimmable
Emergency	Without
Insulation Class	II
Lamp Holder	LED
Dimmable	No
Colors	F001F23A001 - White
Certificates	
Note	We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire. During the installation and the

## FLOS

maintenance of the fixtures it is important to be careful and avoid damages on the paint coating. Damages on the coating exposed to outdoor conditions or water, could cause corrosion. Chemical substances affect the anticorrosion covering protection. For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges These effects are frequently caused by: • over voltage coming from the mains' network where fixture is connected. • electrostatic discharge (ESD) coming from the environment. The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.











Spot visor F001Z010000

FLO

Spot visor with honeycomb F001Z030000

Spot visor with flood lens F001Z040000 S.P.D. (SURGE PROTECTION DEVICE) F990E00A000