

GUISE

Design by Stefan Diez.

Reference

2288.

Application

Hanging lamps

Installation type

Surface

Description

The hanging version with a diameter of 40 cm, providing a nuanced and elegant light over work surfaces, dining areas and meeting tables.

Diffuser

Borosilicate glass diffuser

Materials

Ceiling rose: Steel


Body: Aluminum

Finish



2288-18 Graphite (ADAPTA RF 9913 WX)

Sketch



Electrical characteristics

1 x LED STRIP 24V 18W

Total 18.0 W



VIBIA



Light source: 3000K CRI >90 1325 lm 118 lm/W

Driver included: CV - Constant Voltage 220-240V 50/60Hz

Electronic dimming 1-10V PUSH

ficha.fichatecnicaproducto.regulacion.opcional DALI or Casambi

Technical characteristics

- Sensor on the LED base

Physical characteristics

0 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0000 m³ /

Gross weight 0.0 kg. / Net weight 0.0 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 38.65 lm/W

Coordinate system : CG

Total flux : 868.47 lm

Maximum value : 348.73 cd

Light position : C=0.00 G=5.00

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

