

# GUISE

Design by Stefan Diez.

## Reference

**2292.**

## Application

Ceiling Lamps

## Installation type

Surface

## Description

Ceiling light. The larger diameter glass cylinder is held vertically, concentrating the light within a lower corona of light. The pattern of striations etched into the borosilicate glass irradiates a general light with a moiré effect of visual interference crowned by a fine halo. The light source is hidden by the upper black profile.

## Diffuser

Borosilicate glass diffuser

## Materials

Ceiling rose: Steel


Body: Aluminum

## Finish



**2292-18** Graphite (ADAPTA RF 9913 WX)

## Sketch



## Electrical characteristics

1 x LED STRIP 24V 12W

Total 12.0 W



# VIBIA



**Light source:** 3000K CRI >90 1325 lm 118 lm/W

**Driver included:** CV - Constant Voltage 110-240V 50/60Hz

**Electronic dimming** 1-10V PUSH

[ficha.fichatecnicaproducto.regulacion.opcional](#) DALI or Casambi

## Technical characteristics

- Sensor on the LED base

## Physical characteristics

0 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0000 m<sup>3</sup> /

Gross weight 0.0 kg. / Net weight 0.0 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 26.02 lm/W

Coordinate system : C=0.00 G=0

Total flux : 398.74 lm

Maximum value : 329.76 cd

Light position : CG

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

