## **GUISE**

Design by Stefan Diez.



Reference

2262.

Application

Wall Lamps

Installation type

Surface

Description

Vibia presents a wall lamp that integrates the LED light with the glass and making it pass through in such a way that it becomes invisible and then allowing it to appear out of nowhere.

Diffuser

Difusor de vidrio borosilicato transparente

**Materials** 


Profile: Aluminum Diffuser: Borosilicate glass

**Finish** 



2262-18 Graphite (ADAPTA RF 9913 WX)

Sketch



**Electrical characteristics** 

1 x LED STRIP 24V 17,2W

Total 17.2 W



**Light source:** 3000K CRI >90 1504 lm 87 lm/W

Fixture: 897.91 lm 40.45 lm/W

Driver included: CC - Constant Current 100-240V 50/60Hz

Electronic dimming Optical sensor

**Technical characteristics** 

- The glass is made of borosilicate. It is typical for the glass to have small air bubbles, some inclusions and tiny scratches. These do not affect the quality or the resistance of the glass.

**Physical characteristics** 

1 Box /  $0.00 \times 0.00 \times 0.00 \text{ m.}$  / Vol.  $0.4327 \text{ m}^3$  / Gross weight 18.0 kg. / Net weight 11.5 kg.

Installation and assembly

Please, see the installation manual

**Light distribution** 

## **General lighting**

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency: 1  ${\it Coordinate \ system: CG}$ Total flux: 897.91 lm

Light position: X=0.00m Y=0.00m Z=2.50m Maximum value : 188.65 cd/klm Light position: C=0.00 G=85.00

Certificates











Isolux: Isolux (Floor)



