

MUSA

Design by Note Design Studio.

VIBIA

Reference

7404.

Application

Table Lamps

Installation type

Surface

Description

Vibia offers a table lamp. The aluminum base captures the light as the small glass sphere and transforms it into a soft illumination.

Diffuser

Mat opal triplex blown-glass diffuser

Materials

Body: Aluminum

Diffuser: Blown-glass

Finish



7404-58 Matt salmon lacquer (NCS S 1010-Y50R)




7404-59 Mink (NCS S 2005-Y50R)



7404-93 Matt white (RAL 9016)

Sketch



Light source: 2700K CRI >90 238 lm 113 lm/W

Fixture: 128.77 lm 39.26 lm/W

Driver included: CC - Constant Current 100-240V 50/60Hz

Electronic dimming Push

Technical characteristics

- Push button on base dimming

- Battery life: from 6 to 18 hours (depending on intensity).

Physical characteristics

1 Box / 0.17 x 0.32 x 0.30 m. / Vol. 0.0163 m³ /

Gross weight 1.4 kg. / Net weight 1.0 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 128.77 lm

Maximum value : 202.26 cd/klm

Light position : C=285.00 G=25.00

Symmetry on the planes : Symmetrical planes

270-90

Isolux : Isolux (Floor)

Light position :

X=0.00m Y=0.00m Z=2.50m

Certificates



Electrical characteristics

1 x LED 2,1W 700mA

Total 2.1 W

