



WEVER & DUCRÉ
LIGHTING

DEEP 1.0 PAR16

112120B0

Project

Type

Notities

Kwantiteit

Datum

ALGEMEEN

Plafond

Ingebouwd

Gitzwart

IP20

Interieur

445 lm

RAL 9005^a

LED

Lamp PAR16

PAR16

Socket GU10

max. 12 W

CRI 90

OPTISCH

Wide Flood

Beam angle 48°

FYSISCH

Diameter 84 mm

Height 102 mm

0.29 kg

draadveren

ELEKTRISCH

100 - 240 V

Totaal aangesloten vermogen 6.5 W

LED inset 6.5 W

PC2

Safety distance 0.3 m

CUTOUT


Diameter 76-79 mm

Min. ceiling thickness 4 mm


Max. ceiling thickness 27 mm

Recessed depth 105 mm

^a RAL-kleuren kunnen lichtjes afwijken
omwille van productieomstandigheden.



LICHTVERDELING





WEVER & DUCRÉ
LIGHTING

DEEP 1.0 PAR16

112120B0

KEGELDIAGRAM

wide flood 48°

h (m)	EO ² (lx)	ø (m)
1	623	0.89
2	156	1.78
3	69	2.67
4	39	3.56
5	25	4.45

LED LAMPEN

PAR16 LED lamp

TYPE	KLEUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Zwart	ø50-58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Zwart	ø50-58	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	Wit	ø50-58	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	Wit	ø50-58	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Zilver	ø50-52	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Zilver	ø50-52	9 0 5 2 2 7 S 4