FUNNEL

Design by .



Reference

2012.

Application

Ceiling Lamps

Installation type

Surface

Description

Light for ceiling or wall fitting. Gives an indirect light which is ideal for creating a cosy atmosphere in any room. Non-dazzle. Available in two finishes: matt white lacquer or matt

Materials

Shade: Aluminum Reflector: Aluminum Wall plate: Steel

Finish



2012-10 White (NCS S 0300-N)



2012-36 Soft Pink (NCS S 1010-Y50R)



2012-47 Green L1 (NCS S 4005-G80Y)



2012-51 Matt gold leaf (Gold)

Sketch



Electrical characteristics

1 x LED PLATE 6,3W 350mA





Total 6.3 W





Light source: 2700K CRI >80 632 lm 100 lm/W

Fixture: 420 lm 67 lm/W

Driver included: CC - Constant Current 350 mA 100-240V 50/60Hz

Electronic dimming NO DIM

Physical characteristics

1 Box / 0.17 x 0.27 x 0.27 m. / Vol. 0.0115 m³ / Gross weight 1.3 kg. / Net weight 1.2 kg.

Installation and assembly

Please, see the installation manual


Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.







Certificates









