

TUBE

Design by Ichiro Iwasaki.

Reference

6105.

Application

Ceiling Lamps

Installation type

Surface

Description

Ceiling lamp defined by its curved sheet aluminium shade lending a visual and material lightweight quality.

Diffuser

Polycarbonate diffuser

Materials

LED support: Aluminum

Ceiling rose: Steel

Finish



6105-10 White (NCS S 0300-N)



6105-15 Grey L2 (NCS S 2500-N)




6105-16 Grey M1 (NCS S 4500-N)



6105-21 Grey D1 (NCS S 7000-N)

Sketch



Electrical characteristics

1 x LED PLATE 20W 700mA

Total 20.0 W



Light source: 2700K CRI >90 2900 lm 145 lm/W

Fixture: 1169.9 lm 58.49 lm/W

Driver included: CC - Constant Current 700 mA 110-240V 50/60Hz

Electronic dimming DALI 1-10V Push

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0807 m³ /

Gross weight 5.5 kg. / Net weight 2.1 kg.

Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Certificates

