



BOXY L 92733 DIM8 B-FG

10726 9228 B-FG

AVAILABLE IN



BLACK-BLACK 10726 9228 B-B

BLACK-FLEMISH BRONZE 10726 9228 B-FBR

BLACK-FLEMISH GOLD 10726 9228 B-FG

BLACK-GOLD MATT 10726 9228 B-MMAT

WHITE-WHITE 10726 9228 W-W



[View on website](#)

General info

| | |
|---------------------------|---|
| LOCATION | indoor |
| INSTALLATION | Ceiling Surface mounted |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0.5 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | REFLECTOR FL-33° INCL.DIMMABLE POWER SUPPLY 350mA-DC |

Electrical info

| | |
|------------------------------|-----------------------|
| ELECTRICAL | 220-240V / 50-60Hz |
| CLASS | II |
| POWER SUPPLY INCLUDED | YES |
| DIM TYPE | mains (phase cut-off) |
| ENERGY CLASS | D |
| CERTIFICATES | CB, EAC, ENEC |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm |
| TM-30 VALUES | Rf: 89 / Rg: 100 |
| SDCM | SDCM1 |
| RISKGROUP | RG1 |
| LM80 | L90B10 > 50000 |
| LED TECHNICS (LIGHT SOURCE) | 753lm // 5,8W // 129lm/W |
| LED TECHNICS (LUMINAIRE) | 601lm // 7W // 90lm/W |

Accessories

- BOXY HONEYCOMB
- BOXY SOFTENING LENS
- BOXY GLASS SBL


BOXY L 92733 DIM8 B-FG

10726 9228 B-FG

For detailed installation instructions, please consult the manual: [10726_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Control gear, ballast and transformers



300 90 004 ED8 WIRELESS CONTROL DIM8

Light altering devices



Ø40



Ø45
1.5

251 70 03 01 B BOXY HONEYCOMB B

251 70 03 01 W BOXY HONEYCOMB W



Ø40



Ø45
1.5

251 70 03 04 B BOXY SOFTENING LENS B

251 70 03 04 W BOXY SOFTENING LENS W



Ø40



Ø45
1.5

251 70 03 05 B BOXY GLASS SBL B

251 70 03 05 W BOXY GLASS SBL W

 DELTALIGHT®

BOXY L 92733 DIM8 B-FG

10726 9228 B-FG

Notes: