



BOXY XL S 92720 DIMI W-B



251 72 21 921 ED1 W-B

AVAILABLE IN

BLACK-BLACK 251 72 21 921 ED1 B-B

WHITE-BLACK 251 72 21 921 ED1 W-B

WHITE-WHITE 251 72 21 921 ED1 W-W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.3
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-20° INCL.DIMMABLE LED POWER SUPPLY 700mA-DC

Electrical info

ELECTRICAL	120-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	1-10V
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 23,2W / CRI>90 (R9: 60) / 2700K / 3031lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	3031lm // 23,2W // 130lm/W
LED TECHNICS (LUMINAIRE)	2647lm // 27W // 99lm/W

Accessories

HONEYCOMB 78
SOFTENING LENS 78
GLASS SBL 78


BOXY XL S 92720 DIM1 W-B

251 72 21 921 ED1 W-B

For detailed installation instructions, please consult the manual: [251_72_21_XXX_ED1_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Control gear, ballast and transformers




300 90 016 ED1 WIRELESS CONTROL 5A DIM1


Light altering devices



201 02 01 B HONEYCOMB 78 B



201 02 04 SOFTENING LENS 78



201 02 05 GLASS SBL 78

Notes: