

BEGA**33 534**

Ceiling and wall luminaire



Project · Reference number

Date

Product data sheet

Application

LED ceiling and wall luminaire with high protection class for a variety of lighting tasks. A luminaire made of die cast aluminium and impact resistant crystal glass.

Product description

Luminaire made of aluminium alloy, aluminium and stainless steel
 Crystal glass with white matt finish
 Silicone gasket
 2 mounting holes \varnothing 4.5 mm
 Distance apart 110 mm
 2 cable entries for through-wiring of mains supply cable \varnothing 7-10.5 mm
 Connecting terminal 2.5² with plug connection
 Earth conductor connection
 LED power supply unit
 220-240 V \sim 0/50-60 Hz
 DC 176-264 V
 Safety class I
 Protection class IP 65
 Dust-tight and protection against water jets
 Impact strength IK07
 Protection against mechanical impacts < 2 joule
 – Safety mark
CE – Conformity mark
 Weight: 1.0 kg

Inrush current

Inrush current: 7 A / 112 μ s
 Maximum number of luminaires of this type per miniature circuit breaker:
 B10A: 38 luminaires
 B16A: 61 luminaires
 C10A: 64 luminaires
 C16A: 102 luminaires

Lamp

Module connected wattage	2.8 W
Luminaire connected wattage	3.9 W
Rated temperature	$t_a = 25$ °C
Ambient temperature	$t_{a \max} = 45$ °C



On request we can offer you modifications for environments with higher temperatures as a customized product.

33 534 K3

Module designation	LED-0337/830
Colour temperature	3000 K
Colour rendering index	CRI > 80
Module luminous flux	580 lm
Luminaire luminous flux	338 lm
Luminaire luminous efficiency	86,7 lm/W

33 534 K4

Module designation	LED-0337/840
Colour temperature	4000 K
Colour rendering index	CRI > 80
Module luminous flux	600 lm
Luminaire luminous flux	349 lm
Luminaire luminous efficiency	89,5 lm/W



Service life · Ambient temperature

Ambient temperature $t_a = 25$ °C
 LED psu: > 50,000 h
 LED module: > 200,000 h (L80B50)
 100,000 h (L90B50)

Ambient temperature $t_a = 45$ °C
 LED psu: 50,000 h
 LED module: > 200,000 h (L80B50)
 100,000 h (L90B50)

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Article No. 33 534

LED colour temperature optionally 3000 K or 4000 K
 3000 K – Article number + **K3**
 4000 K – Article number + **K4**

Colour graphite or silver
 graphite – article number
 silver – article number + **A**

Light distribution

