



BOXY R 93033 B-MMAT

251 70 811 932 B-MMAT



AVAILABLE IN

BLACK-BLACK 251 70 811 932 B-B

BLACK-GOLD MATT 251 70 811 932 B-MMAT

WHITE-BLACK 251 70 811 932 W-B

WHITE-WHITE 251 70 811 932 W-W



 [View on website](#)

General info

| | |
|---------------------------|--|
| LOCATION | indoor |
| INSTALLATION | Ceiling Surface mounted |
| INGRESS PROTECTION | IP40 |
| WEIGHT (KG) | 0.6 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | REFLECTOR FL-33° INCL.LED POWER SUPPLY 500mA-DC |

Electrical info

| | |
|------------------------------|--------------------|
| ELECTRICAL | 110-240V / 50-60Hz |
| CLASS | I |
| POWER SUPPLY INCLUDED | YES |
| DIM TYPE | non-dimmable |
| ENERGY CLASS | D |

Lightsource info

| | |
|------------------------------------|---|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm |
| TM-30 VALUES | Rf: 90 / Rg: 99 |
| SDCM | SDCM1 |
| RISKGROUP | RG1 |
| LM80 | L90B10 > 50000 |
| LED TECHNICS (LIGHT SOURCE) | 1089lm // 8,6W // 127lm/W |
| LED TECHNICS (LUMINAIRE) | 852lm // 10W // 86lm/W |

Options

COVERSET R100

Accessories

BOXY HONEYCOMB
BOXY SOFTENING LENS
BOXY GLASS SBL


BOXY R 93033 B-MMAT

251 70 811 932 B-MMAT

For detailed installation instructions, please consult the manual: [251_70_811_XXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Coversets



204 00 100 B COVERSET R 100 B

204 00 100 W COVERSET R 100 W

Light altering devices



Ø40

251 70 03 01 B BOXY HONEYCOMB B



Ø45

251 70 03 01 W BOXY HONEYCOMB W



Ø40

251 70 03 04 B BOXY SOFTENING LENS B



Ø45

251 70 03 04 W BOXY SOFTENING LENS W



Ø40

251 70 03 05 B BOXY GLASS SBL B



Ø45

251 70 03 05 W BOXY GLASS SBL W

BOXY R 93033 B-MMAT

251 70 811 932 B-MMAT

Notes: