



## BOXY R 93033 DIM8 B-MMAT

251 70 811 932 ED8 B-MMAT

AVAILABLE IN

**BLACK-BLACK** 251 70 811 932 ED8 B-B



**BLACK-FLEMISH BRONZE** 251 70 811 932 ED8 B-FBR

**BLACK-FLEMISH GOLD** 251 70 811 932 ED8 B-FG

**BLACK-GOLD MATT** 251 70 811 932 ED8 B-MMAT

**WHITE-BLACK** 251 70 811 932 ED8 W-B

**WHITE-WHITE** 251 70 811 932 ED8 W-W



 [View on website](#)

### General info

<b>LOCATION</b>	indoor-outdoor
<b>INSTALLATION</b>	Ceiling Surface mounted
<b>INGRESS PROTECTION</b>	IP53
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK03
<b>WEIGHT (KG)</b>	0.6
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	II
<b>POWER SUPPLY INCLUDED</b>	YES
<b>DIM TYPE</b>	mains (phase cut-off)
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	CB, EAC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
<b>TM-30 VALUES</b>	Rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>LED TECHNICS (LIGHT SOURCE)</b>	1089lm // 8,6W // 127lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	852lm // 10W // 86lm/W

### Accessories

BOXY HONEYCOMB  
BOXY SOFTENING LENS  
BOXY GLASS SBL

# BOXY R 93033 DIM8 B-MMAT


251 70 811 932 ED8 B-MMAT

For detailed installation instructions, please consult the manual: [251\\_70\\_811\\_XXX\\_ED8\\_HAND.pdf](#)

## FINISH YOUR SPECIFICATION

### Control gear, ballast and transformers

---



**300 90 004 ED8** WIRELESS CONTROL DIM8

### Light altering devices

---



Ø40

**251 70 03 01 B** BOXY HONEYCOMB B



Ø45

**251 70 03 01 W** BOXY HONEYCOMB W



Ø40

**251 70 03 04 B** BOXY SOFTENING LENS B



Ø45

**251 70 03 04 W** BOXY SOFTENING LENS W



Ø40

**251 70 03 05 B** BOXY GLASS SBL B



Ø45

**251 70 03 05 W** BOXY GLASS SBL W



**BOXY R 93033 DIM8 B-MMAT**

251 70 811 932 ED8 B-MMAT

Notes: