



BOXY R 93033 W-B

251 70 811 932 W-B



AVAILABLE IN

BLACK-BLACK 251 70 811 932 B-B

BLACK-GOLD MATT 251 70 811 932 B-MMAT

WHITE-BLACK 251 70 811 932 W-B

WHITE-WHITE 251 70 811 932 W-W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP40
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	110-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	852lm // 10W // 86lm/W

Options

COVERSET R100

Accessories

BOXY HONEYCOMB
BOXY SOFTENING LENS
BOXY GLASS SBL


BOXY R 93033 W-B

251 70 811 932 W-B

For detailed installation instructions, please consult the manual: [251_70_811_XXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Coversets



204 00 100 B COVERSET R 100 B

204 00 100 W COVERSET R 100 W

Light altering devices



Ø40

251 70 03 01 B BOXY HONEYCOMB B



Ø45

251 70 03 01 W BOXY HONEYCOMB W



Ø40

251 70 03 04 B BOXY SOFTENING LENS B



Ø45

251 70 03 04 W BOXY SOFTENING LENS W



Ø40

251 70 03 05 B BOXY GLASS SBL B



Ø45

251 70 03 05 W BOXY GLASS SBL W

 DELTALIGHT®

BOXY R 93033 W-B

251 70 811 932 W-B

Notes: