



## BOXY R 92733 W-W

251 70 811 922 W-W



AVAILABLE IN

**BLACK-BLACK** 251 70 811 922 B-B

**BLACK-GOLD MATT** 251 70 811 922 B-MMAT

**WHITE-BLACK** 251 70 811 922 W-B

**WHITE-WHITE** 251 70 811 922 W-W



[View on website](#)

### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted
<b>INGRESS PROTECTION</b>	IP40
<b>WEIGHT (KG)</b>	0.6
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	REFLECTOR FL-33° INCL.LED POWER SUPPLY 500mA-DC

### Electrical info

<b>ELECTRICAL</b>	110-240V / 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY INCLUDED</b>	YES
<b>DIM TYPE</b>	non-dimmable
<b>ENERGY CLASS</b>	D

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
<b>TM-30 VALUES</b>	Rf: 89 / Rg: 100
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>LED TECHNICS (LIGHT SOURCE)</b>	1041lm // 8,6W // 121lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	815lm // 10W // 82lm/W

### Options

COVERSET R100

### Accessories

BOXY HONEYCOMB  
BOXY SOFTENING LENS  
BOXY GLASS SBL

**BOXY R 92733 W-W**


251 70 811 922 W-W

For detailed installation instructions, please consult the manual: [251\\_70\\_811\\_XXX\\_HAND.pdf](#)

**FINISH YOUR SPECIFICATION**

**Coversets**

---



**204 00 100 B** COVERSET R 100 B

**204 00 100 W** COVERSET R 100 W

**Light altering devices**

---



Ø40

**251 70 03 01 B** BOXY HONEYCOMB B



Ø45

**251 70 03 01 W** BOXY HONEYCOMB W



Ø40

**251 70 03 04 B** BOXY SOFTENING LENS B



Ø45

**251 70 03 04 W** BOXY SOFTENING LENS W



Ø40

**251 70 03 05 B** BOXY GLASS SBL B



Ø45

**251 70 03 05 W** BOXY GLASS SBL W

 DELTALIGHT®

**BOXY R 92733 W-W**

251 70 811 922 W-W

Notes: