



BOXY R OK 92733 DIM8 W-W

251 77 811 922 ED8 W-W



AVAILABLE IN

BLACK-BLACK 251 77 811 922 ED8 B-B

BLACK-GOLD MATT 251 77 811 922 ED8 B-MMAT

WHITE-BLACK 251 77 811 922 ED8 W-B

WHITE-WHITE 251 77 811 922 ED8 W-W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	743lm // 10W // 75lm/W


For detailed installation instructions, please consult the manual: [251_77_811_XXX_HAND.pdf](#)

BOXY R OK 92733 DIM8 W-W

251 77 811 922 ED8 W-W

FINISH YOUR SPECIFICATION

Control gear, ballast and transformers



300 90 004 ED8 WIRELESS CONTROL DIM8



Notes: