





BOXY XL R 93020 DIM1 W-B
251 71 21 931 ED1 W-B

AVAILABLE IN
BLACK-BLACK 251 71 21 931 ED1 B-B
WHITE-BLACK 251 71 21 931 ED1 W-B
WHITE-WHITE 251 71 21 931 ED1 W-W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-20° INCL.DIMMABLE LED POWER SUPPLY 700mA-DC

Electrical info	
ELECTRICAL	120-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	1-10V
ENERGY CLASS	C
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 23,2W / CRI>90 (R9: 52) / 3000K / 3169lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	3169lm // 23,2W // 136lm/W
LED TECHNICS (LUMINAIRE)	2756lm // 27W // 103lm/W

Accessories	
HONEYCOMB 78	
SOFTENING LENS 78	
GLASS SBL 78	


BOXY XL R 93020 DIM1 W-B

251 71 21 931 ED1 W-B

For detailed installation instructions, please consult the manual: [251_71_21_XXX_ED1_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Control gear, ballast and transformers




300 90 016 ED1 WIRELESS CONTROL 5A DIM1

☐


Light altering devices



201 02 01 B HONEYCOMB 78 B

☐

201 02 04 SOFTENING LENS 78

☐

201 02 05 GLASS SBL 78

☐

Notes: