



BOXY XL R C 92720 W-W



251 73 21 921 W-W

AVAILABLE IN

BLACK-BLACK 251 73 21 921 B-B

WHITE-BLACK 251 73 21 921 W-B

WHITE-WHITE 251 73 21 921 W-W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.8
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-20° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC INCL.1 x CABLE SUSPENSION SINGLE AUTO. 1.6m INCL.1 x CABLE 2 x 0,75mm ²

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 16,3W / CRI>90 (R9: 60) / 2700K / 2209lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2209lm // 16,3W // 136lm/W
LED TECHNICS (LUMINAIRE)	1921lm // 19W // 102lm/W

Options

COVERSET R 90-100
SUSPENSION + CONNECTION TRIMLESS

Accessories

HONEYCOMB 78
SOFTENING LENS 78

CLASS SBL 78

 DELTALIGHT®

BOXY XL R C 92720 W-W

251 73 21 921 W-W


For detailed installation instructions, please consult the manual: [251_73_21_XXX_HAND.pdf](#)

BOXY XL R C 92720 W-W

251 73 21 921 W-W


FINISH YOUR SPECIFICATION

Control gear, ballast and transformers



300 90 004 ED8 WIRELESS CONTROL DIM8


Coversets



204 00 100 B COVERSET R 100 B

204 00 100 W COVERSET R 100 W

Suspension parts




328 10 02 SUSPENSION + CONNECTION TRIMLESS O.F.A.

BOXY XL R C 92720 W-W

251 73 21 921 W-W

Light altering devices



201 02 01 B HONEYCOMB 78 B

Ø78



201 02 04 SOFTENING LENS 78

Ø78



201 02 05 GLASS SBL 78

Ø78

Notes: