

HALO

Design by Martin Azua.

Reference

2355.

Application

Hanging lamps

Installation type

Surface

Description

Hanging lamp. Providing an ambient or indirect light through its vertical methacrylate diffuser. The diffuser is supported by a fine grade steel structure. By combining several units of differing heights a more dynamic effect can be achieved for larger spaces.

Diffuser

Methacrylate diffuser

Materials

Diffuser: Polycarbonate

LED support: Aluminum

Pendant structure: Steel

Ceiling rose: Steel

Finish




2355-11 Black (NCS S 8500N)



2355-20 Gold finish (Gold)

Sketch



Electrical characteristics

3 x LED STRIP 24V 15,3W

Total 45.9 W



VIBIA



Light source: 3000K CRI >80 2274.17 lm 98.87 lm/W

Fixture: 1157.34 lm 50.31 lm/W

Driver included: CC - Constant Current 220-240V 50/60Hz

Electronic dimming 1-10V

ficha.fichatecnicaproducto.regulacion.opcional DALI or Casambi

Technical characteristics

- Surface

Physical characteristics

0 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0000 m³ /

Gross weight 0.0 kg. / Net weight 0.0 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Certificates

