


## IC Ceiling Wall 1 Outdoor Burgundy Red

■ F012H00C037 - Burgundy Red




Wall- or ceiling-mounted light fitting with diffuse light for exterior use available in two sizes. Frame in brushed stainless steel, brushed brass finish or painted opaque black or burgundy. The structure of the fitting is treated with a chemical conversion process for effective resistance to atmospheric agents. Special attention is recommended during installation and maintenance to prevent damage to the powder coating. Opalescent diffuser in shiny white translucent blown glass. The light comes with seals for IP-rated connection.

### Main specifications

<b>Lamp category</b>	LED retrofit
<b>Mountings</b>	Ceiling and wall surface
<b>Environment</b>	Outdoor

### Optical

<b>Lighting type</b>	Direct
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light



Beam Angle: 0°

h(m)	E(lx)	D(m)
1	57	
2	14	
3	6	
4	4	
5	0	

Luminous flux luminaire  
700 lm

### Electrical


<b>Frequency (Hz)</b>	50-60
<b>Voltage (V)</b>	220-240
<b>Dimmable</b>	Yes
<b>Emergency</b>	Without
<b>Insulation class</b>	I

### Physical


<b>Color</b>	Burgundy Red
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	2.2

### Note

Bulb not included. LED: max 8W - E14



### Certification / Marking



## IC Ceiling Wall 1 Outdoor Burgundy Red



---

LED 8W E14 800lm 3000K cod. RF26565  
[e] Dimmable  
RF26565

---

LED 8W E14 700lm 2700K cod. RF26767  
[e] Dimmable  
RF26767