

TEMPO

Design by Lievore Altherr.

Reference

5778.

Application

Hanging lamps

Installation type

Surface

Description

Tempo pendant lamps are a design by Lievore Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

Diffuser

Blow-glass diffuser

Materials

LED support: Aluminum

Diffuser: Blown-glass

Ceiling rose: Steel

Finish



5778-18 Matt graphite lacquer (ADAPTA RF 9913 WX)



5778-35 Matt brick lacquer (NCS S 4040-Y70R)




5778-58 Matt cream lacquer (RAL 7044)



5778-62 Matt green lacquer (NCS S 3010-G20Y)

Sketch



Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



VIBIA LIGHTING, S.L.U. Barcelona, 72 - 74. 08820 El Prat de Llobregat (Barcelona - Spain). Tel 934 796 970. Fax 934 796 973.
vibia@vibia.com www.vibia.com

VIBIA



Light source: 2700K CRI >90 440.81 lm 110 lm/W

Fixture: 261.43 lm 65.35 lm/W

Driver included: CC - Constant Current 350 mA 110-240V 50/60Hz

Electronic dimming 1-10V Push

ficha.fichatecnicaproducto.regulacion.opcional DALI or Casambi

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0454 m³ /

Gross weight 4.0 kg. / Net weight 2.5 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 47.27 lm/W

Isolux : Floor

Coordinate system : CG

Light position :

Total flux : 261.43 lm

X=0.00m Y=0.00m Z=2.50m

Maximum value : 190.70 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Certificates



