

TEMPO

Design by Lievore Altherr.

Reference

5760.

Application

Wall Lamps

Installation type

Surface

Description

Wall lamp. An adjustable rod emerges from the base attached to the wall, with blown glass diffuser and a tensing cable that permits precise adjustment of the height of the glass tulip. Connection with plug. LED light source.

Diffuser

Blow-glass diffuser

Materials

Body: Steel

Diffuser: Blown-glass

LED support: Aluminum

Finish



5760-18 Graphite (ADAPTA RF 9913 WX)



5760-35 Matt brick lacquer (NCS S 4040-Y70R)




5760-58 Cream (RAL 7044)



5760-62 Matt green lacquer (NCS S 3010-G20Y)

Sketch



Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



Light source: 2700K CRI >90 440.81 lm 110 lm/W

Fixture: 302.04 lm 75.4 lm/W

Driver included: CC - Constant Current 380 mA 220-240V 50/60Hz

Electronic dimming Push

Technical characteristics

- Dimmer switch on the cable

Physical characteristics

2 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0877 m³ /

Gross weight 4.5 kg. / Net weight 2.4 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Certificates



