TEMPO

Design by Lievore Altherr.



Reference

5763.

Application

Wall Lamps

Installation type

Built-in

Description

Wall lamp composed of a stylized profile attached to the wall and topped by a blown glass diffuser that gives the piece a delicate image. Connection without plug. LED light source.

Diffuser

Blow-glass diffuser

Materials

Body: Steel

Diffuser: Blown-glass LED support: Aluminum

Finish



5763-18 Graphite (ADAPTA RF 9913 WX)



5763-35 Matt brick lacquer (NCS S 4040-Y70R)



5763-58 Cream (RAL 7044)



5763-62 Matt green lacquer (NCS S 3010-G20Y)

Sketch



Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



Light source: 2700K CRI >90 440.81 lm 110 lm/W

Fixture: 301.62 lm 75.4 lm/W

Driver included: CC - Constant Current 350 mA 220-240V 50/60Hz

Electronic dimming 1-10V Push

Technical characteristics

- Built-in version

Physical characteristics

2 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0565 $m^3\,/$ Gross weight 4.3 kg. / Net weight 2.3 kg.

Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Certificates









