

# TEMPO

Design by Lieve Altherr.

## Reference

**5770.**

## Application

Hanging lamps

## Installation type

Surface

## Description

Tempo pendant lamps are a design by Lieve Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

## Diffuser

Blow-glass diffuser

## Materials

LED support: Aluminum

Diffuser: Blown-glass

Ceiling rose: Steel

## Finish



**5770-18** Matt graphite lacquer (ADAPTA RF 9913 WX)



**5770-35** Matt brick lacquer (NCS S 4040-Y70R)




**5770-58** Matt cream lacquer (RAL 7044)



**5770-62** Matt green lacquer (NCS S 3010-G20Y)

## Sketch



## Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



VIBIA LIGHTING, S.L.U. Barcelona, 72 - 74. 08820 El Prat de Llobregat (Barcelona - Spain). Tel 934 796 970. Fax 934 796 973.  
vibia@vibia.com www.vibia.com

# VIBIA



**Light source:** 2700K CRI >90 440.81 lm 110 lm/W

**Fixture:** 301.62 lm 75.4 lm/W

**Driver included:** CC - Constant Current 350 mA 110-240V 50/60Hz

**Electronic dimming** 1-10V Push

ficha.fichatecnicaproducto.regulacion.opcional DALI or Casambi

## Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0163 m<sup>3</sup> /

Gross weight 2.5 kg. / Net weight 2.0 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 54.76 lm/W

Isolux : Floor

Coordinate system : CG

Light position :

Total flux : 301.62 lm

X=0.00m Y=0.00m Z=2.50m

Maximum value : 235.37 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

## Certificates



