

# FLOS

09.8300.AH Glossy Grey

**Oblique**

NEW

Designed by Vincent Van Duysen, 2020




LED - Top LED - 8W - 479lm - 2700K - CRI> 90 - Beam° 35

Professional table lamp with patented asymmetric optics. External power supply included with 1500-mm cable. USB-C connection integrated into the base of the device to recharge compatible devices. Driver input: 24 V

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



## Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Table               |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 8                   |
| System power (W)       | 18                  |
| Source flux (lm)       | 754                 |
| System flux (lm)       | 479                 |

## Physical

|                 |             |
|-----------------|-------------|
| Colour          | Glossy Grey |
| Orientation     | Fixed       |
| Net weight (kg) | 0.75        |
| IP internal     | 20          |
| IP external     | 20          |

## Download

Mounting instructions [↓ PDF](#)

## Photometric Files

LDT / IES [↓ ZIP](#)

## Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)



<https://professional.flos.com/en/global/product/oblique-09.8300.ah/>


09.8300.AH

©2022 Flos - P.IVA 00290820174 - 4/5/2025

[professional.flos.com](https://professional.flos.com) | [info@flos.com](mailto:info@flos.com) 1/2

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Schematic light drawing



|             |       |       |
|-------------|-------|-------|
| Beam Angle: | 35°   |       |
| h(m)        | E(lx) | D(m)  |
| 1           | 229   | 2.18  |
| 2           | 57    | 4.36  |
| 3           | 25    | 6.54  |
| 4           | 14    | 8.72  |
| 5           | 9     | 10.90 |

Photometric

|                          |                            |
|--------------------------|----------------------------|
| Lighting type            | Direct                     |
| Light distribution       | Asymmetric                 |
| CCT (K)                  | 2700                       |
| CRI>                     | 90                         |
| LED Life / Failure Ratio | L90B10 > 50.000h (Tc=85°C) |
| Beam angle C0-180 (°)    | 35                         |
| Beam angle C90-270 (°)   | 46                         |

Electrical

|                           |                 |
|---------------------------|-----------------|
| Insulation class          | III             |
| Power supply              | Remote included |
| Dimmable                  | Yes             |
| Power supply type         | Dimmable        |
| Emergency                 | No              |
| Induction recharge QI     | No              |
| Charging socket/connector | USB-C           |