



**slat spike** Design: Klaus Nolting

für unbefestigte Beet- und Grünflächen for unpaved beds and greens



**Lichttechnik:**  
230V Power LED  
2700K  
L70/50.000 h

dimmbar

**Anschluss:**  
5 m Zuleitung  
(H05RN-F 3G0,75) inkl.  
Schutzkontaktstecker  
anschlussfertig

ortsveränderlich

**Material:**  
Kopf: Aluminiumguss  
pulverbeschichtet  
Spieß: Edelstahl  
pulverbeschichtet  
Sicherheitsglas satiniert

**Schutzart:**  
IP65

**Lichtrichtung:**



**light technology:**  
230V Power LED  
2700K  
L70/50.000 h

dimmable


**connection:**  
5 m supply cable  
(H05RN-F 3G0,75)  
incl. safety plug  
ready to connect

movable




**material:**  
head: aluminium die-casting  
powder-coated  
spike: stainless steel  
powder-coated  
safety glass satined

**protection class:**  
IP65

**light direction:**



Größe in mm  
size in mm

Farbe colour	Art.-Nr. item no.	Systemleistung system performance
 anthracite RAL 7016	91030-27-AN	8 W/280 lm
 cool brown	91030-27-CB	8 W/280 lm
 deep black RAL 9005	91030-27-BL	8 W/280 lm

+ Anschluss optional mit IP44.de connect. Produktdetails  
connection with IP44.de connect as an option. product details