



Minimalist, slim pendant for use in a Zip rail system. Perfectly suited above the kitchen counter, the dining table or in a window. Made of powder-coated, die-cast aluminium and available in black or white finish. The retracted light source causes minimal glare and can be dimmed with phase control dimmer.

Tube Micro black and white comes with a black bezel ring, including a gold bezel. Tube Micro white also comes with a white bezel ring.

Light technic

Direct
LED (not exchangeable) (1)
220-240V
7W
2000-2800K, 2700K or 3000K
Ra 98 or Ra>95
SDCM:2 or SDCM:3
L90/B10>50,000 at Ta=25°C
Beam angle: 40°
Energy class: A

Control gear

Trailing edge dimming

Protection

Class II, IP20, Ta=25°C, CE

Optic

Reflector medium

Material and finish

Housing: Aluminium
Colour: Black (RAL 9004) or White (RAL 9003)
Optic: Polycarbonat (PC)

Mounting and connection

Surface






Zip Tube Micro Pendant









Product- and environment images



For line drawing dimensions please see each single article codes on next page

Article	Protection	Control gear	Mounting/Connection	Dimensions (mm)
2000-2800K				
	320631	Class II	Trailing edge	Surface, Indoor
	Zip Tube Micro Pendant Black	IP20	dimming	
	Pendant 340lm 2000-2800K Ra>95 Trailing edge dimming 7W LED 49 lm/W SDCM:3 L90/B10>50,000 Beam: 40°, Direct, Reflector medium			
	320627	Class II	Trailing edge	Surface, Indoor
	Zip Tube Micro Pendant White	IP20	dimming	
	Pendant 340lm 2000-2800K Ra>95 Trailing edge dimming 7W LED 49 lm/W SDCM:3 L90/B10>50,000 Beam: 40°, Direct, Reflector medium			
2700K				
	320624	Class II	Trailing edge	Surface, Indoor
	Zip Tube Micro Pendant White	IP20	dimming	
	Pendant 330lm 2700K Ra 98 Trailing edge dimming 7W LED 48 lm/W SDCM:2 L90/B10>50,000 Beam: 40°, Direct, Reflector medium			
	320628	Class II	Trailing edge	Surface, Indoor
	Zip Tube Micro Pendant Black	IP20	dimming	
	Pendant 330lm 2700K Ra 98 Trailing edge dimming 7W LED 48 lm/W SDCM:2 L90/B10>50,000 Beam: 40°, Direct, Reflector medium			
3000K				
	320625	Class II	Trailing edge	Surface, Indoor
	Zip Tube Micro Pendant White	IP20	dimming	
	Pendant 340lm 3000K Ra 98 Trailing edge dimming 7W LED 49 lm/W SDCM:2 L90/B10>50,000 Beam: 40°, Direct, Reflector medium			

Article	Protection	Control gear	Mounting/Connection	Dimensions (mm)
 <p>320629 Zip Tube Micro Pendant Black Pendant 340lm 3000K Ra 98 Trailing edge dimming 7W LED 49 lm/W SDCM:2 L90/B10>50,000 Beam: 40°, Direct, Reflector medium</p>	<p>Class II IP20</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor</p>	
Accessories				
 <p>312330 Pendant Ceiling Box White Ceiling Box for Pendant Steel</p>				<p>Ø102</p>
 <p>3163 Bell Black Ceiling Box for Pendant</p>				<p>Ø114</p>
 <p>3108 Shopline White Pendant Adapter</p>				
 <p>3164 Bell White Ceiling Box for Pendant</p>				<p>Ø114</p>
 <p>3109 Shopline Black Pendant Adapter</p>				