



Zip Tube Mini is a stylish and minimalist spotlight adapted for the Zip 230V 1-circuit system, a more powerful version than the Micro in the same family, but which can be combined on the same rail. The basic design has a black baffle, but the inner ring can be unscrewed and replaced with a white or gold version (accessory). This allows for creative individual designs. The black provides less dazzle, the gold gives a warmer light, and the white reflects the most.

Light technic

Direct
LED (not exchangeable) (1)
220-240V
17W
2700K or 3000K
Ra 98
SDCM:2
L90/B10>50,000 at 0
Beam angle: 40°
Energy class: A+

Control gear

Trailing edge dimming

Protection

Class II, IP20, CE

Optic

Reflector medium

Material and finish








Housing: Aluminium
Colour: Black (RAL 9004) or White (RAL 9003)
Optic: Polycarbonat (PC)

Mounting and connection

Surface

Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions (mm)
2700K				
	320612 Zip Tube Mini Black 830lm 2700K Ra 98 Trailing edge dimming 17W LED 49 lm/W SDCM:2 L90/B10>50,000 Beam: 40°, Direct, Reflector medium	Class II IP20	Trailing edge dimming	Surface, Indoor
	320608 Zip Tube Mini White 830lm 2700K Ra 98 Trailing edge dimming 17W LED 49 lm/W SDCM:2 L90/B10>50,000 Beam: 40°, Direct, Reflector medium	Class II IP20	Trailing edge dimming	Surface, Indoor
3000K				
	320613 Zip Tube Mini Black 870lm 3000K Ra 98 Trailing edge dimming 17W LED 52 lm/W SDCM:2 L90/B10>50,000 Beam: 40°, Direct, Reflector medium	Class II IP20	Trailing edge dimming	Surface, Indoor
	320609 Zip Tube Mini White 870lm 3000K Ra 98 Trailing edge dimming 17W LED 52 lm/W SDCM:2 L90/B10>50,000 Beam: 40°, Direct, Reflector medium	Class II IP20	Trailing edge dimming	Surface, Indoor
Accessories				
	320684 Zip Tube Mini Black Ø59 Bezel Aluminium			Ø55
	320683 Zip Tube Mini White Ø59 Bezel Aluminium			Ø55
	320685 Zip Tube Mini Gold Accessory Aluminium			Ø55