



Zip Tube Mini Pendant can be used as both 1-circuit and 3-circuit depending on the adapter. If you choose rail-mounted, the pendant luminaire can also be combined with spotlights in the same product family. It can also be fitted as a single, with ceiling roses available. The tubular luminaire with its fabric cable is suitable for an endless number of locations, such as bar tables, kitchen counters, cafés and windows. The raised light source gives minimal dazzling and a focused light. The basic design has a black baffle, but the inner ring can be unscrewed and replaced with a white or gold version (accessory). This allows for creative individual designs. The black provides less dazzle, the gold gives a warmer light, and the white reflects the most.

Light technic

Direct

LED (not exchangeable) (1)

220-240V

17W

2700K or 3000K

Ra 98

SDCM:2

L90/B10>50,000 at 0 or L90/B10>50,000 at Ta=25°C

Beam angle: 40°

Energy class: A+

Control gear

Trailing edge dimming

Protection

Class II, IP20, Ta=25°C, CE

Optic

Reflector medium

Material and finish

Housing: Aluminium

Colour: Black (RAL 9004) or White (RAL 9003)

Optic: Polycarbonat (PC)

Mounting and connection







Surface






Zip Tube Mini Pendant



Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions (mm)
2700K				
	320640 Zip Tube Mini Pendant White Pendant 830lm 2700K Ra 98 Trailing edge dimming 17W LED 49 lm/W SDCM:2 L90/B10>50,000 Beam: 40°, Direct, Reflector medium	Class II IP20	Trailing edge dimming	Surface, Indoor Cable 3m Ø59
	320644 Zip Tube Mini Pendant Black Pendant 830lm 2700K Ra 98 Trailing edge dimming 17W LED 49 lm/W SDCM:2 L90/B10>50,000 Beam: 40°, Direct, Reflector medium	Class II IP20	Trailing edge dimming	Surface, Indoor Cable 3m Ø59
3000K				
	320645 Zip Tube Mini Pendant Black Pendant 870lm 3000K Ra 98 Trailing edge dimming 17W LED 52 lm/W SDCM:2 L90/B10>50,000 Beam: 40°, Direct, Reflector medium	Class II IP20	Trailing edge dimming	Surface, Indoor Cable 3m Ø59
	320641 Zip Tube Mini Pendant White Pendant 870lm 3000K Ra 98 Trailing edge dimming 17W LED 52 lm/W SDCM:2 L90/B10>50,000 Beam: 40°, Direct, Reflector medium	Class II IP20	Trailing edge dimming	Surface, Indoor Cable 3m Ø59
Accessories				
	320684 Zip Tube Mini Black Ø59 Bezel Aluminium			Ø55
	3163 Bell Black Ceiling Box for Pendant			Ø114

Article	Protection	Control gear	Mounting/Connection	Dimensions (mm)
 3108 Shopline White Pendant Adapter				
 3164 Bell White Ceiling Box for Pendant				Ø114
 3109 Shopline Black Pendant Adapter				
 320683 Zip Tube Mini White Ø59 Bezel Aluminium				Ø55
 320685 Zip Tube Mini Gold Accessory Aluminium				Ø55