

STRUCTURAL

Design by Arik Levy.

VIBIA

Reference

2620.

Application

Wall Lamps

Installation type

Surface

Description

Wall light that marks coordinates with a rectilinear language, connects points of light in space, relates planes and underlines the architectural dimension. Indirect lighting and composition based on volumes clarify light and shade.

Diffuser

Polycarbonate diffuser

Materials

Body: Aluminum
Diffuser: Polycarbonate
Profile: Aluminum

Finish




2620-15 Grey L2 (NCS S 2500-N)



2620-21 Grey D1 (NCS S 7000-N)

Sketch



Electrical characteristics

2 x LED PLATE 24V 6W

Total 12.0 W



Light source: 3000K CRI >90

Driver included: CC - Constant Current 110-240V 50/60Hz

Electronic dimming 1-10V

ficha.fichatecnicaproducto.regulacion.opcional DALI or Casambi

Technical characteristics

- Only one main input by square box 16x16cm.

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0000 m³ /
Gross weight 0.0 kg. / Net weight 0.0 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting - opaque shade

Lamp for general lighting with an opaque shade and distributing light upwards and/or downwards mainly.



Photometric data

Certificates

