

# STRUCTURAL

Design by Arik Levy.

# VIBIA

## Reference

**2642.**

## Application

Ceiling Lamps

## Installation type

Surface

## Description

Ceiling light where different cubic volumes meet or expand to provide flexible solutions, maintaining spatial order.

## Diffuser

Polycarbonate diffuser

## Materials

Body: Aluminum  
Diffuser: Polycarbonate  
Profile: Aluminum

## Finish




**2642-15** Grey L2 (NCS S 2500-N)



**2642-21** Grey D1 (NCS S 7000-N)

## Sketch



## Electrical characteristics

1 x LED PLATE 24V 15W

AND

1 x LED PLATE 24V 30W



Total 45.0 W



**Light source:** 3000K CRI >90

**Driver included:** CC - Constant Current 110-240V 50/60Hz

**Electronic dimming** 1-10V

ficha.fichatecnicaproducto.regulacion.opcional DALI or Casambi

## Technical characteristics

- Main input by the biggest box

## Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0000 m<sup>3</sup> /

Gross weight 0.0 kg. / Net weight 0.0 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting - opaque shade

Lamp for general lighting with an opaque shade and distributing light upwards and/or downwards mainly.



## Photometric data

## Certificates

