

STRUCTURAL

Design by Arik Levy.

VIBIA

Reference

2647.

Application

Ceiling Lamps

Installation type

Surface

Description

Ceiling light where different cubic volumes meet or expand to provide flexible solutions, maintaining spatial order.

Diffuser

Polycarbonate diffuser

Materials

Body: Aluminum
Diffuser: Polycarbonate
Profile: Aluminum

Finish




2647-15 Grey L2 (NCS S 2500-N)



2647-21 Grey D1 (NCS S 7000-N)

Sketch



Electrical characteristics

1 x LED PLATE 24V 9W
AND
1 x LED PLATE 24V 15W
AND
1 x LED PLATE 24V 30W



Total 54.0 W



Light source: 3000K CRI >90

Driver included: CC - Constant Current 110-240V 50/60Hz

Electronic dimming 1-10V

ficha.fichatecnicaproducto.regulacion.opcional DALI or Casambi

Technical characteristics

- Main input by the biggest box

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0000 m³ /

Gross weight 0.0 kg. / Net weight 0.0 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting - opaque shade

Lamp for general lighting with an opaque shade and distributing light upwards and/or downwards mainly.



Photometric data

Certificates

