

Name **PHARE SINGLE**
 Number **N135**
 Collection **ARTON**

TEKNA

General

Location Indoor
 Main material Brass/ glass
 IP rating IP20
 Class I
 Bathroom zone Zone 3
 Voltage 230V
 Driver required Integrated
 Cable length (m) .
 Dimensions (mm) 75x45x45
 Mounting method Wall bracket
 Gross weight (kg) .
 Net weight (kg) .
 Packaging (mm) .
 Energy Efficiency % .



Lamp





Included

Light source Filament LED
 Number of light sources 1
 Socket type S14d
 Bulb shape Linear Lamp
 Max lamp length (mm) 300 / 500
 Power consumption 3.5W / 4W / 6W / 7W / 8W / 10W / 12W
 Luminous flux 250lm / 260lm / 320lm / 350lm / 400lm / 480lm / 500lm / 510lm / 560lm
 Color temperature 2200K / 2700K
 CRI 90
 Lifetime 20.000h / 25.000h / 30.000h
 Beam angle 270° / 360°

Electrical

Switch (type) .
 Battery No
 Dimmable Yes
 Dimming range <20% to 100%
 Dimming method Phase dim
 Supply frequency 50Hz / 60Hz
 Driver/ballast voltage 230V
 Efficiency .

Finishes

-  Brushed Chrome Plated Brass
-  Brushed Nickel Plated Brass
-  Custom Color
-  Dark Bronze
-  Polished Brass
-  Polished Chrome Plated Brass
-  Polished Nickel Plated Brass

