## Flat

Design by Ichiro Iwasaki.



Reference

5955.

Application

Floor Lamps

Installation type

Surface

Description

The Flat floor lamp offers multiple functionality; material and light are integrated in a single body. The Flat collection contains various planes of light that rise up to become self-illuminating supports.

Diffuser

Polycarbonate diffuser

Materials

Body: Steel Base: Steel Head: Aluminium Reflector: Aluminum

Finish



**5955-11** Black (NCS S 8500N)




**5955-37** Terra Red (NCS S 4040-Y70R)



**5955-47** Green L1 (NCS S 4005-G80Y)

Sketch



**Electrical characteristics** 

1 x LED PLATE 7W 400mA

Total 7.0 W





Light source: 2700K CRI >90 1200 lm 171 lm/W

Driver included: CC - Constant Current 400 mA 100-240V 50/60Hz

Electronic dimming PUSH

**Technical characteristics** 

- 24V transformer at plug

Physical characteristics

0 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0000 m<sup>3</sup> / Gross weight 0.0 kg. / Net weight 0.0 kg.

Installation and assembly

Please, see the installation manual

Light distribution

## **Indirect lighting**

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data

Certificates











