Flat Design by Ichiro Iwasaki.

VIBIA

Reference

5957.

Application Floor Lamps

Installation type Surface

Description

The Flat floor lamp offers multiple functionality; material and light are integrated in a single body. The Flat collection contains various planes of light that rise up to become self-illuminating supports.

Diffuser

Polycarbonate diffuser


Materials Body: Steel Base: Steel Head: Aluminium Reflector: Aluminum

Finish

5957-13 Grey L1 (NCS S 1000-N)

5957-47 Green L1 (NCS S 4005-G80Y)

Sketch



Electrical characteristics 1 x LED PLATE 7W 400mA

A⁺

Total 7.0 W



Light source: 2700K CRI >90 1200 lm 171 lm/W Driver included: CC - Constant Current 400 mA 100-240V 50/60Hz

Electronic dimming PUSH

Technical characteristics - 24V transformer at plug

- 24v transionner at plug

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.1267 m³ / Gross weight 6.1 kg. / Net weight 4.5 kg.

Installation and assembly Please, see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data

Certificates



VIBIA LIGHTING, S.L.U. C/ Progrés 4-6, 08850 - Gavà (Barcelona - Spain). Tel 934 796 970. Fax 934 796 973. vibia@vibia.com www.vibia.com