



WEVER & DUCRÉ
LIGHTING

HEXO SUSPENDED 3.0 PAR16

215220G0

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Suspended

Gold

IP20

Interior

405^a, 445^b, 450^c lm

LED

Lamp PAR16

PAR16

Socket GU10

max. 12 W

L70 / 50000 h

OPTICAL

Beam angle 48°

PHYSICAL

Diameter 77 mm

Height 300 mm

0.74 kg

incl. 2.5 m suspension

ELECTRICAL

100 - 240 V

Total connected power 8.8^c, 8.9^b, 10^a

W


PC1

Safety distance 0.3 m


^a LED 1800-2850K CRI 90 silver

^b LED 3000K CRI 80 white

^c LED 2700K CRI 80 white



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

HEXO SUSPENDED 3.0 PAR16

215220G0

CONE DIAGRAM

LED 2700K CRI ≥ 80 White

h (m)	EO° (lx)	ø (m)
1	632	0.89
2	158	1.78
3	70	2.67
4	39	3.56
5	25	4.45

LED LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Jet Black	ø50·58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Jet Black	ø50·58	9 0 1 2 2 8 B 5
2700K >80 CRI GU10	Signal White	ø50·58	9 0 1 2 2 8 W 2
2700K >90 CRI GU10	Signal White	ø50·58	9 0 1 2 2 8 W 3
3000K >80 CRI GU10	Signal White	ø50·58	9 0 1 2 2 8 W 4


PAR16 LED Lamp | Ambient

TYPE	Ø · H (MM)	ORDERCODE
1800-2850K >90 CRI GU10	ø50·58	9 0 1 2 2 9 S 9

SUSPENSION OPTIONS

Invisible Ceiling Suspension System

TYPE	L · W · H (MM)	ORDERCODE
Plasterkit	156·60·26	9 0 0 1 5 1 9 5



Single Suspension

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
Ceiling Base round	Signal Black	ø84·29	9 0 0 5 2 0 2 1
Ceiling Base round	Pure White	ø84·29	9 0 0 5 2 0 2 2
Ceiling Base semi recessed	Pure White	ø84·72	9 0 0 5 2 0 2 6
Ceiling Base semi recessed	Signal Black	ø84·72	9 0 0 5 2 0 2 7

