



Bit | On/Off Driver



	range	output	input	eff.	PF	surge
<b>99243</b>	6.5W DC arrayLED	700mA 10V	100~240V AC	80%	0.6 C	0.5 kV
<b>99370</b>	10W DC arrayLED	300mA 36V	100~240V AC	80%	0.6 C	0.5 kV

Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.


Slim | On/Off Driver



	range	output	input	eff.	PF	surge
<b>99307</b>	0.7-1.5W DC powerLEDs	220mA 6.6V	198~264V AC	80%	0.6 C	4 kV
<b>83007</b>	2-5W DC powerLEDs	220mA 20V	198~264V AC	80%	0.9 C	2 kV
<b>89144</b>	1-2W DC powerLEDs 1-2.5W DC topLED	350mA 6.6V	198~264V AC	80%	0.6 C	4 kV
<b>89145</b>	3-6W DC powerLEDs 3.5-7W DC topLED	350mA 20V	198~264V AC	80%	0.6 C	4 kV
<b>99375</b>	6-12W DC powerLEDs	350mA 40V	198~264V AC	80%	0.9 C	2 kV
<b>99195</b>	1.5-3W DC powerLEDs	500mA 6.6V	198~264V AC	80%	0.6 C	4 kV
<b>89146</b>	3-5W DC powerLEDs	500mA 10V	198~264V AC	80%	0.6 C	4 kV
<b>99377</b>	4.5-10W DC powerLEDs	500mA 20V	198~264V AC	80%	0.9 C	2 kV
<b>89147</b>	2-4W DC powerLEDs	630mA 6.6V	198~264V AC	80%	0.6 C	4 kV
<b>99376</b>	6-12W DC powerLEDs	630mA 20V	198~264V AC	80%	0.9 C	2 kV

Smartwave™: excellent efficiency, a long operating life, surge protection and high PF. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Simon | On/Off Driver



	range	output	input	eff.	PF	surge
<b>99198</b>	8W DC arrayLED 3-7W DC powerLEDs 8W DC topLED	220mA 39V	198~264V AC	89%	0.9 C	4 kV
<b>99126</b>	13.5W DC topLED 6-12W DC powerLEDs	350mA 39V	198~264V AC	89%	0.9 C	4 kV
<b>99128</b>	4.5-9W DC powerLEDs	500mA 20V	198~264V AC	89%	0.9 C	4 kV
<b>99129</b>	6-12W DC powerLEDs	630mA 20V	198~264V AC	89%	0.9 C	4 kV
<b>99734</b>	8W DC arrayLED 11W DC arrayLED 15W DC arrayLED	220mA 37V 300mA 37V 400mA 37V	198~264V AC	82%	0.96	2 kV
<b>99735</b>	6W DC powerLEDs 6.5-7W DC arrayLED 10W DC powerLEDs	500mA 12V 700mA 9-12V 800mA 12V	198~264V AC	74%	0.96	2 kV

	range	output	input	eff.	PF	surge
<b>99260</b>	13W DC topLED	350mA 36V	190~250V AC	89%	0.9 C	4 kV
<b>99740</b>	8W DC arrayLED 11W DC arrayLED 15W DC arrayLED	220mA 37V 300mA 37V 400mA 37V	190~250V AC	82%	0.96	2 kV

Smartwave™: excellent efficiency, a long operating life, surge protection and high PF. Protection against overheating, overloading, open circuits and short-circuits along the output line. For codes 99734, 99735 and 99740, the current is selected via the jumper.



Easy Plug connector included for codes **99260, 99740**