



WEVER & DUCRÉ
LIGHTING

FINLIN 1.0

370184B3

GENERAL

Wall
Surface
Jet Black
IP20
Interior
350 lm
9005^a

LED

2700 K
3-step binning

OPTICAL

Opal

PHYSICAL

Diameter 9 mm
Height 623 mm
0.15 kg

ELECTRICAL

incl. PS | phase-cut dim
220 - 240 V
Total connected power 6 W
LED Inset 6 W
PC2
Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.


Project

Type

Notes

Quantity

Date





WEVER & DUCRÉ
LIGHTING

FINLIN 1.0

370184B3

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.93	0.89	0.86	0.83
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.