






# MICK on track

## 48V SYSTEM



DESIGNED BY  
S&R CORNELISSEN



### 1.0

LED 9.5W | 48V | COB 3-step  
aluminium powder coated  
PC adapter

0.22kg IP20  $\approx 0.3^\circ$   $\approx 18^\circ$

$\approx 90^\circ$   $\approx 360^\circ$

non dim

	CODE
	159462J
	159462K

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	325	>90	3
3000K	355	>90	5

### 1.0

LED 9.5W | 48V | COB 3-step  
aluminium powder coated  
PC adapter

0.22kg IP20  $\approx 0.3^\circ$   $\approx 18^\circ$

$\approx 90^\circ$   $\approx 360^\circ$

DALI dim

	CODE
	159465J
	159465K

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	325	>90	3
3000K	355	>90	5

dim options on page 341

### 2.0

2x LED 9.5W | 48V | COB 3-step  
aluminium powder coated  
PC adapter

0.44kg IP20  $\approx 0.3^\circ$   $\approx 18^\circ$

$\approx 90^\circ$   $\approx 360^\circ$

non dim

	CODE
	159562J
	159562K

	CODE
	159565J
	159565K

DALI dim

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x325	>90	3
3000K	2x355	>90	5

dim options on page 341