



WEVER & DUCRÉ
LIGHTING

TAPE 8.0

722474D5

Project
Type
Notes
Quantity
Date

GENERAL

Floor
 Surface
 Dark Grey Texture
 IP65
 Exterior
 420 lm

LED

3000 K
 CRI 90
 L95 / 50000 h
 3-step binning

OPTICAL

Wide Flood

PHYSICAL


Length 180 mm
 Width 60 mm
 Height 800 mm
 3.1 kg

ELECTRICAL


incl. PS | phase-cut dim
 220 - 240 V
 Total connected power 8 W
 PC1
 Safety distance 0.3 m



IP65 $\le 0,3\text{m}$



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

TAPE 8.0

722474D5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

GROUND SPIKE

Ground Spike

TYPE	L · W · H (MM)	ORDERCODE
TAPE PACE	58-70-356	9 0 0 1 3 1 0 2