

ROB 2.6

701284W3

GENERAL

Ceiling
Surface
Signal White
IP44
Interior
1400 lm
9003^a

LED

2700 K
CRI 90
L90 / 50000 h
3-step binning

OPTICAL

Opal

PHYSICAL

Diameter 260 mm
Height 60 mm
1.2 kg

ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 13 W
PC1
Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.

Project _____

Type _____


Notes _____

Quantity _____


Date _____



IP44    0.3 m



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

ROB 2.6

701284W3

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.93	0.91	0.9
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Electrical

DIMMER

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
DIMMER FOR SWITCH	Signal Black	18·48·46	9 0 0 1 9 0 1 7
DIMMER DIN RAIL	Pure White	55·17·90	9 0 0 1 9 0 1 8