



WEVER & DUCRÉ
LIGHTING

ROB 3.5

701384W3

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Surface

Signal White

IP44

Interior

2250 lm

9003^a

LED

2700 K

CRI 90

L90 / 50000 h

3-step binning

OPTICAL

Opal

PHYSICAL

Diameter 350 mm

Height 60 mm

1.9 kg

ELECTRICAL

phase-cut dim

220 - 240 V


Total connected power 36 W

PC1


Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.

IP44    0.3m



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

ROB 3.5

701384W3

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.93	0.91	0.9
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Electrical

DIMMER

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
DIMMER FOR SWITCH	Signal Black	18·48·46	9 0 0 1 9 0 1 7
DIMMER DIN RAIL	Pure White	55·17·90	9 0 0 1 9 0 1 8