



WEVER & DUCRÉ
LIGHTING

ROBY 3.5

135384B3

GENERAL

Ceiling

Surface

Jet Black

IP44

Interior

1680 lm

9005^a

LED

2700 K

3-step binning

OPTICAL

Opal

PHYSICAL

Diameter 355 mm

Height 60 mm

2.5 kg

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 32 W

PC1

Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.

Project

Type


Notes

Quantity

Date



IP44    0.3 m





WEVER & DUCRÉ
LIGHTING

ROBY 3.5

135384B3

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.91	0.86	0.82	0.77
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Electrical

DIMMER

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
DIMMER FOR SWITCH	Signal Black	18·48·46	9 0 0 1 9 0 1 7
DIMMER DIN RAIL	Pure White	55·17·90	9 0 0 1 9 0 1 8