



WEVER & DUCRÉ
LIGHTING

MIRBI long 3.0

329384W5

Project

Type

Notes

Quantity

Date

GENERAL

Wall

Surface

Signal White + Clear/Opal PMMA

IP44

Interior

610^a to 840^b lm

9003^c

LED

3000 K

3-step binning

OPTICAL

Wide Flood

PHYSICAL

Length 900 mm

Width 40 mm

Height 40 mm

2.3 kg

ELECTRICAL

incl. PS output selector | phase-cut

dim

220 - 240 V

Total connected power 12^a to 18^b W

PC1

Safety distance 0.3 m

13^a to 20^b W/m


^a Low Output

^b High Output

^c RAL Palette colors may deviate slightly due to production conditions.



IP44   





WEVER & DUCRÉ
LIGHTING

MIRBI long 3.0

329384W5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.97	0.93	0.9	0.87	0.84
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.